


TUNG-SOL

THYRATRON
MINIATURE TYPE



GLASS BULB


COATED UNIPOTENTIAL CATHODE

HEATER

2.5 VOLTS 0.650 AMPERE

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW
MINIATURE BUTTON
7 PIN BASE

THE 2C4 IS A THYRATRON DESIGNED FOR USE IN COMPACT, LIGHT-WEIGHT, PORTABLE EQUIPMENT. IT IS RECOMMENDED THAT NO MATERIAL BE PERMITTED TO OBSTRUCT THE HOLE IN THE BASE SOCKET AS THIS TYPE MAY BE MANUFACTURED WITH THE EXHAUST-TUBE TIP AT THE BASE END.

RATINGS

INTERPRETED ACCORDING TO RMA STANDARD NB-210

| | | |
|---|-------|---------|
| HEATER VOLTAGE | 2.5 | VOLTS |
| HEATER CURRENT | 0.650 | AMP. |
| HEATING TIME (MINIMUM) | 30 | SECONDS |
| MAXIMUM VOLTAGE BETWEEN ELEMENTS | 450 | VOLTS |
| AVERAGE ANODE CURRENT ^A | 5.0 | MA. |
| PEAK ANODE CURRENT | 20 | MA. |
| TUBE VOLTAGE ^A DROP AT 5.0 MA. (APPROX.) | 16 | VOLTS |

^A AVERAGED OVER PERIOD OF NOT MORE THAN 30 SECONDS.

→ INDICATES A CHANGE OR ADDITION.

